

The new SAVOX® HC is a compact and light weight helmet-com unit for professionals working in extreme and hazardous conditions. The SAVOX® HC provides instant, clear and reliable "hands-free" communication, increasing personal safety and work efficiency, allowing full concentration on the actual task.

Thanks to the unique arm/strap fastening system the SAVOX $^{\otimes}$ HC-1 easily mounts in almost any type of helmet without any tools. The convenient bone conduction microphone is voice sensitive and makes a perfect combination with a breathing mask. The SAVOX $^{\otimes}$ HC is the ideal communication solution for fire and rescue, special task operations - simply whenever using a helmet.

The intrinsically safe SAVOX® HC connects to most SAVOX® com-control/PTT units adapting to most types of two-way radios.

helmet-comeunit bone conduction microphone





Specifications

Weight 85g

Size 40 x 160 mm

Microphone vibration sensitive, impedance approx. 3500 ohm @1 kHz,

noise cancellation 30 dB

Speaker impedance 32 ohm (HC-1)

Cable coiled (flame retardant): Ø 4mm/380mm

straight (flashover proof): Ø 4mm/750mm

Connector 4-pole quick release plug
Operation temperature -25...+63 °C (continuous)

Supply voltage 3,0...10,0 VDC

 $\begin{array}{ll} \mbox{Humidity} & 95\%\mbox{RH,} +63\mbox{ °C for 500 hours} \\ \mbox{ESD,EMI immunity} & \mbox{confirms with the EN 301 489-1} \end{array}$

Compatibility most SAVOX® com-control/push to talk units

Intrinsic safety ATEX (EX) Approved

Options SAVOX® HC-1 coiled cable/short headband

SAVOX® HC-1 coiled cable/long headband* SAVOX® HC-1FP straight cable/long headband* SAVOX® HC-2 coiled cable/dual speaker

SAVOX® HC-2FP straight cable/dual speaker*

(*ATEX Approved)









www.savox.com